Number	009
Subject	Auto Operation using PC-P2HTE and PC-ART Remote Controller
Date	February 2009

Currently all Utopia and Set Free systems arrive with "Auto" operation disabled. This is because "Auto" is mostly used in the UK due to our wider ambient temperature fluctuations

Please follow these instructions to enable "Auto" operation.

Instruction	Status
1) Ensure Remote Controller is "OFF"	
2) Press "OK" and "RESET" together for	Service status "01" will appear in
more than three seconds	bottom window
MODE FAN SPEED TMER RESET	
3) Press " OK "	Address " 00 " " 00 " will show in top window
MODE FAN SPEED TIMER RESET	
4) Press the Temperature Down button once	Address display in top window will change from " 00 " " 00 " to " AA " " AA " (all units)
HITACHI	



Technical Bulletin

5) Press " OK "	Indication " B1 " will appear in top right window. The " AA " " AA " display will be replaced by " 00 " status
6) Press " SCHEDULE " continuously to scroll through to status " B8 "	Indication " B8 " will appear in top right window.
MODE FAN SPEED TMER RESET	(" B8 " is the Indication for Auto. " 00 " is the status which is Auto Operation - OFF .)
7) Press " OK "	Status "00" will change to "01".
	"01" is Auto Operation – On
8) Press "RESET"	Remote controller will return to normal operation mode.
MODE FAN SPEED TMER RESET	
9) Turn remote controller "ON"	Normal Operation. (Press MODE button to ensure AUTO is working)

