Air Conditioning

Product Information

MSZ-FH Inverter Heat Pump Wall Mounted System Making a
World of
Difference



MSZ-FH Inverter Heat Pump

Wall Mounted System

The MSZ-FH series is our most energy efficient M Series wall mounted unit to date.

These high efficiency models feature the Plasma Duo filter system. They also offer industry leading noise levels and have a distinctively styled front panel that not only looks appealing but also helps to make cleaning of the unit easier. Also incorporated is a '3D I-See Sensor', providing even temperature distribution and further reducing energy consumption.

Key Features

- Swing Vane Mode with Auto Vane Shutter
- Infra-red remote controller
- Econo Cool allows set temperature to be raised by 2°C without any loss of comfort and a 20% gain in energy efficiency
- Auto-Restart
- Quiet operation
- Auto-Changeover
- Hot Start draught prevention
- Plasma Duo filter system
- Quick clean design
- Replace Technology available
- I-See Sensor



Air Conditioning | Heating Ventilation | Controls



Product Information

Air Conditioning

MSZ-FH Inverter Heat Pump Wall Mounted System

Making a World of Difference









| MSZ-FH - INDOOR UNITS | | MSZ-FH25VE | MSZ-FH35VE |
|---------------------------------|---------------------------------------|---------------------------------|---------------------------------|
| CAPACITY (kW) | Heating (nominal) | 3.2 (1.8-5.5) | 4.0 (1.0-6.3) |
| | Cooling (nominal) | 2.5 (1.4-3.5) | 3.5 (0.8-4.0) |
| | Heating (UK) | 2.65 (1.49-4.57) | 3.3 (0.8-5.2) |
| | Cooling (UK) | 2.48 (1.38-3.47) | 3.47 (0.79-3.97) |
| SHF (nominal & UK) | | 0.95 | 0.84 |
| COP / EER (nominal) | | 5.52 / 5.15 | 5.00 / 4.27 |
| SCOP / SEER (BSEN14825) | | 5.1 / 9.1 | 5.1 / 8.9 |
| ErP ENERGY EFFICIENCY CLASS | Heating/Cooling | A+++ / A+++ | A+++ / A+++ |
| AIRFLOW (m³/min) | Heating - SLo-Lo-Mi-Hi-Shi | 4.0-4.7-6.4-9.2-13.2 | 4.0-4.7-6.4-9.2-13.2 |
| | Cooling - SLo-Lo-Mi-Hi-Shi | 3.9-4.7-6.3-8.6-11.6 | 3.9-4.7-6.3-8.6-11.6 |
| PIPE SIZE mm (in) | Gas | 9.52 (3/8") | 9.52 (3/8") |
| | Liquid | 6.35 (1/4") | 6.35 (1/4") |
| SOUND PRESSURE LEVEL (dBA) | Heating/Cooling - Silent-Lo-Mi-Hi-Shi | 20-24-29-36-44 / 20-23-29-36-42 | 21-24-29-36-44 / 21-24-29-36-42 |
| SOUND POWER LEVEL (dBA) | | 58 | 58 |
| DIMENSIONS (mm) | Width x Depth x Height | 925 x 234 x 305 | 925 x 234 x 305 |
| WEIGHT (kg) | | 13.5 | 13.5 |
| ELECTRICAL SUPPLY | | Fed by Outdoor Unit | Fed by Outdoor Unit |
| FUSE RATING (BS88) - HRC (A) | | 6 | 6 |
| INTERCONNECTING CABLE No. CORES | | 4 | 4 |

| MUZ-FH - OUTDOOR UNITS | | MUZ-FH25VE | MUZ-FH35VE |
|--|---------------------------|-----------------|-----------------|
| SOUND PRESSURE LEVEL (dBA) | Heating/Cooling | 49 / 46 | 50 / 49 |
| SOUND POWER LEVEL (dBA) | Cooling | 60 | 61 |
| WEIGHT (kg) | | 37 | 37 |
| DIMENSIONS (mm) | Width x Depth x Height | 800 x 285 x 550 | 800 x 285 x 550 |
| ELECTRICAL SUPPLY | | 220-240v, 50Hz | 220-240v, 50Hz |
| PHASE | | Single | Single |
| SYSTEM POWER INPUT (kW) | Heating/Cooling (nominal) | 0.580 / 0.485 | 0.800 / 0.820 |
| | Heating/Cooling (UK) | 0.520 / 0.400 | 0.760 / 0.690 |
| STARTING CURRENT (A) | | 2.9 | 3.9 |
| SYSTEM RUNNING CURRENT (A) Heating/Cooling [MAX] | | 2.9 / 2.6 [9.6] | 3.9 / 3.8 [9.6] |
| FUSE RATING (BS88) - HRC (A) | | 10 | 10 |
| MAINS CABLE No. CORES | | 3 | 3 |
| MAX PIPE LENGTH (m) | | 20 | 20 |
| MAX HEIGHT DIFFERENCE (m) | | 12 | 12 |
| CHARGE R410A (kg) - 7m | | 1.15 | 1.15 |



Telephone: 01707 282880

email: airconditioning@meuk.mee.com web: www.airconditioning.mitsubishielectric.co.uk

UNITED KINGDOM Mitsubishi Electric Europe Living Environmental Systems Division Travellers Lane, Hatfield, Hertfordshire, AL10 8XB, England General Enquiries Telephone: 01707 282880 Fax: 01707 278881

IRELAND Mitsubishi Electric Europe Westgate Business Park, Ballymount, Dublin 24, Ireland Telephone: Dublin (01) 419 8800 Fax: Dublin (01) 419 8890 International code: (003531)

Country of origin: United Kingdom – Japan – Thaland – Malaysia. @Mitsubish Electric Europe 2013. Mitsubish i Bloctric are trademarks of Mitsubish Electric Europe B.V. The company reserves the right to nake any variation in technical specification to the equipment described, or to withdraw or replace products without prior notification or public announcement. Mitsubish Electric is constantly developing and improving its products. All descriptions, illustrations, drawings and specifications in this publication present only general particulars and shall not form part of any contract. All goods are supplied subject to the Company's General Conditions of Sale, a copy of which is available on request. Third-party product and brand names may be trademarks or registered trademarks of their respective owners.











Mitsubishi Electric's commitment to the environment



Follow us @green_gateway



Connect with Green Gateway



You mitsubishielectric2