

—
Set Free Σ

Cooling & Heating

HITACHI

-

Key Selling point

- **Single module** : up to 24HP
- **Performance** : SEER up to 8,03
SCOP up to 5,06
- **Smooth drive control** : Precise control in 0,1 Hz increments of inverter frequency with expended working range down to 10% of maximum capacity
- **Wide operation range** : -10 to 52°C in cooling mode / -20 to 15°C in heating mode
- **Silent mode operation** : Lowers sound power/pressure level by three steps
- **Single CHBOX** : No need to connect the liquid pipe
- **Multi CHBOX** : Compact, no drain pan needed
- **Easy access** to electrical parts with access door



-

Key Specification point

- **Compressor** : 100% DC inverter scroll compressor with higher performance at low load operation
- **Static pressure** : Adjustable up to 80 Pa
- **Heat exchanger** : Composed of aluminum fins and several striated copper tubes, and an anti-corrosion treatment
- **Smart Refrigerant Temperature Control** : System will automatically adjust the evaporating temperature based on room conditions to improve comfort and efficiency
- **Defrosting** : Indoor unit fans are stopped during defrosting to prevent cold draft
- **2-3 pipes** : No need to replace an outdoor unit 2 pipes system when 3 pipes is needed
- **Smart building ready** : 3 inputs and 2 outputs

Cooling & Heating



—
Set Free Σ

Cooling & Heating

HITACHI