

## Shirokuma Wall Mounted HITACHI

Hitachi's Shirokuma systems are a premium range of stylish and highly-efficient wall mounted split systems. In ice white with a frosted sheer front panel combined with a matte and glass finish cabinet to reflect light, Shirokuma looks good from any angle.



### Features and Benefits

- SCOP of 4.7 (A++) and SEER of 8.5 (A+++) for exceptional seasonal efficiency
- 24hour, 7-Day Infra Red Controller
- Pre-charged to max pipe run of 20 meters (25-35 models)
- Pre-charged to max 30 metre pipe run (50 models)
- Heating or Cooling only lock
- Elegant design complements any interior
- Low noise levels courtesy of Optional Hard-Wired Controller with 7-Day Timer
- Group Control and remote operation and fault integration for BMS application.
- Antibacterial Sanitizing Nano Titanium Wasabi filter for high air quality.
- Energy saving sensor adjust heating and cooling levels as room occupancy changes. Super Low fan speed
- Capacities from 2.5kW to 5.8kW
- SCOP of 4.72 (A++)
- SEER of 8.5 (A+++) for exceptional seasonal efficiency
- Elegant design complements any interior
- Low noise levels courtesy of Super Low fan speed
- Antibacterial Sanitizing Nano Titanium Wasabi filter for high air quality
- Energy saving sensor adjust heating and cooling levels as room occupancy changes
- Weekly timer
- Compatible with H-LINK control and CS Net Web.
- POWER/WIRING: Power supply to Outdoor Unit with 3C + E interconnecting cable. Note that this is 240vAC plus Comms.
- R32 Refrigerant

# HITACHI

Model Reference		Nom. Cool (kw)	Nom. Heat (kw)	Max Pipe (m)	EuP Lot 10 Energy Rating		Fuse (Amps)	Pipe Gas	Pipe Liquid	R22 Replace?	Power Supply
Indoor	Outdoor				SCOP	SEER					
RAK-25RXB	RAC-25WXB	2.50	3.20	20	4.70	8.50	16	3/8	1/4	No	Single
RAK-35RXB	RAC-35WXB	3.50	4.00	20	4.70	8.50	16	3/8	1/4	No	Single
RAK-50RXB	RAC-50WXB	5.00	5.80	30	4.50	7.20	25	1/2	1/4	No	Single