

Aquarea Air Smart fan coils

NEW Aquarea Air Smart fan coil wall-mounted


Slim chassis profile, only 128 mm.

DC Inverter – maximising comfort and energy savings.

Modulated air flow.

New 2025

Optional



Model (the complete model codes are shown in the table below)	Total capacity		Air flow	Dimension	Weight	
	Cooling ¹⁾	Heating ²⁾				
	Med	Med	Max	H x W x D		
	kW	kW	m³/h	mm	kg	
1ph	P-FMM10	0,88	0,98	228	335 x 815 x 128	14
	P-FMM15	1,08	1,30	331	335 x 1015 x 128	16
	P-FMM20	1,21	1,49	440	335 x 1215 x 128	19
	P-FMM40	2,66	3,04	788	335 x 1215 x 215	24

Water connections information

Aquarea Air Smart fan coils	10	15	20	40
Hydraulic connections type	Eurokonus		Eurokonus	Eurokonus
Hydraulic connections	Inch 3/4	3/4	3/4	3/4

1) According to Eurovent standard. Air: 27 °C DB/19 °C WB, chilled water: 7 °C/12 °C. 3) According to Eurovent standard. Air: 20 °C, hot water: 45 °C/40 °C.

Option 1. Standard configurations with built-in accessories

Fan coil with on-board display and wireless IR control

Right-hand piping, built-in 3 way valve	RRP £
P-FMM10DC-QNE	751
P-FMM15DC-QNE	811
P-FMM20DC-QNE	880
P-FMM40DC-QNE	975

Fan coil with wall-mounted control

Right-hand piping, built-in 3 way valve			RRP £
P-FMM10DC-RNE			766
P-FMM15DC-RNE			827
P-FMM20DC-RNE			895
P-FMM40DC-RNE			1,051
Control (required, to be ordered separately)	With Modbus	PCZ-EEB749	126
	With integrated Wi-Fi	PCZ-EFB749	153

Option 2. Configure your own Aquarea Air Smart fan coil wall-mounted unit

Fan coil with on-board display and wireless IR control

Left-hand piping	RRP £	Right-hand piping	RRP £
P-FMM10SC-Q0E	636	P-FMM10DC-Q0E	595
P-FMM15SC-Q0E	697	P-FMM15DC-Q0E	655
P-FMM20SC-Q0E	766	P-FMM20DC-Q0E	724
—	—	P-FMM40DC-Q0E	838

Fan coil with wall-mounted control

Left-hand piping	RRP £	Right-hand piping	RRP £
P-FMM10SC-R0E	622	P-FMM10DC-R0E	609
P-FMM15SC-R0E	682	P-FMM15DC-R0E	671
P-FMM20SC-R0E	751	P-FMM20DC-R0E	739
—	—	P-FMM40DC-R0E	914
Control (required, to be ordered separately)	With Modbus PCZ-EEB749	126	
	With integrated Wi-Fi PCZ-EFB749	153	

Fan coil with PCB for analog control (0-10 V)

Left-hand piping	RRP £	Right-hand piping	RRP £
P-FMM10SC-V0E	622	P-FMM10DC-V0E	595
P-FMM15SC-V0E	682	P-FMM15DC-V0E	655
P-FMM20SC-V0E	751	P-FMM20DC-V0E	724
—	—	P-FMM40DC-V0E	838

Valve kits (optional)	RRP £
PCZ-V30688 3 way valve with motor for models 10, 15, 20	157
PCZ-V30718 3 way valve with motor for model 40	138

Valve kits (optional)	RRP £
PCZ-V20687 2 way valve with motor for models 10, 15, 20	130
PCZ-V20139 2 way valve with motor for model 40	123


Control options.

On-board display with Modbus.



Wall-mounted control with Modbus or integrated Wi-Fi.

PCZ-EEB749 /
PCZ-EFB749



PCB for analog control (0-10 V).

