

Aquarea Air Smart fan coils

NEW Aquarea Air Smart fan coil ducted multi zone thin / ducted multi zone

Fan coil ducted units with cooling and heating.

Cooling capacity: 0,5 to 7,6 kW.

Heating capacity: 0,5 to 8,52 kW.

New 2025

Optional



Model [the complete model codes are shown in the table below]	Total capacity		Air flow	Maximum static pressure	Dimension	Weight	
	Cooling ¹⁾	Heating ²⁾					
	Med	Med	Max		H x W x D		
	kW	kW	m³/h	Pa	mm	kg	
Ducted multi zone thin							
1ph	P-FTQ30	1,97	2,11	480	100	185 x 790 x 575	41
	P-FTQ45	2,97	3,19	720	100	185 x 990 x 575	45
	P-FTQ60	3,68	5,76	960	100	185 x 1190 x 575	54
	P-FTQ65	4,15	4,75	1200	100	185 x 1440 x 575	56
Ducted multi zone							
1ph	P-FSQ30	3,80	3,90	810	100	240 x 790 x 695	43
	P-FSQ45	3,77	4,16	1215	100	240 x 990 x 695	47
	P-FSQ60	4,87	5,42	1620	100	240 x 1190 x 695	56
	P-FSQ75	6,31	6,87	2025	100	240 x 1440 x 695	67

Water connections information		Ducted multi zone thin				Ducted multi zone			
Aquarea Air Smart fan coils		30	45	60	65	30	45	60	75
Hydraulic connections type		Eurokonus	Eurokonus	Eurokonus	Eurokonus	Eurokonus	Eurokonus	Eurokonus	Eurokonus
Hydraulic connections	Inch	3/4	3/4	3/4	3/4	3/4	3/4	3/4	3/4
Condensate drainage connection	mm	20	20	20	20	20	20	20	20
Intake air connection	mm	160	160	160	160	160	160	160	160
Return air connection (base x height)	mm	630 x 100	830 x 100	1030 x 100	1320 x 100	630 x 150	830 x 150	1030 x 150	1320 x 150

1) According to Eurovent standard. Air: 27 °C DB/19 °C WB, chilled water: 7 °C/12 °C. 2) According to Eurovent standard. Air: 20 °C, hot water: 45 °C/40 °C.

Configure your own Aquarea Air Smart fan coil ducted multi zone thin / ducted multi zone unit

Fan coil with wall-mounted control			
Left-hand piping	RRP €	Right-hand piping	RRP €
P-FTQ30005-RE	1,185	P-FTQ30R05-RE	1,158
P-FTQ45005-RE	1,786	P-FTQ45R05-RE	1,759
P-FTQ60005-RE	2,006	P-FTQ60R05-RE	1,980
P-FTQ65005-RE	2,768	P-FTQ65R05-RE	2,741
P-FSQ30005-RE	1,223	P-FSQ30R05-RE	1,196
P-FSQ45005-RE	1,824	P-FSQ45R05-RE	1,797
P-FSQ60005-RE	2,045	P-FSQ60R05-RE	2,018
P-FSQ75005-RE	2,813	P-FSQ75R05-RE	2,787
Control (required, to be ordered separately)	With Modbus	PCZ-EEB749	126
	With integrated Wi-Fi	PCZ-EFB749	153

Fan coil with PCB for analog control (0-10 V)			
Left-hand piping	RRP €	Right-hand piping	RRP €
P-FTQ30005-JE	1,010	P-FTQ30R05-JE	983
P-FTQ45005-JE	1,512	P-FTQ45R05-JE	1,485
P-FTQ60005-JE	1,679	P-FTQ60R05-JE	1,652
P-FTQ65005-JE	2,387	P-FTQ65R05-JE	2,360
P-FSQ30005-JE	1,048	P-FSQ30R05-JE	1,021
P-FSQ45005-JE	1,550	P-FSQ45R05-JE	1,523
P-FSQ60005-JE	1,701	P-FSQ60R05-JE	1,676
P-FSQ75005-JE	2,425	P-FSQ75R05-JE	2,398

Valve kits (optional)	RRP €
PCZ-V30361 3 way valve with motor	150

Valve kits (optional)	RRP €
PCZ-V20139 2 way valve with motor	123

Control options.

Wall-mounted control with Modbus or integrated Wi-Fi.

PCZ-EEB749 /
PCZ-EFB749



PCB for analog control (0-10 V).

