

THE PACi WALL MOUNTED UNITS WITH STYLISH MATT COLOR

- Modern design with flat face and compact size
- Stylish matt white color
- DC FAN for better efficiency and control
- Six directional piping outlet
- New Comfort Cloud control
- Easy connection and control of external fan or ERV using the connector PAW-FDC on the indoor unit PCB. The external device can be controlled by the remote control of the Panasonic indoor unit



Refrigerant gas R32 that shows a drastic reduction in the value of Global Warming Potential (GWP). — Exceptional Seasonal cooling efficiency based on the ErP regulation. — Exceptional Seasonal heating efficiency based on the ErP regulation. — Inverter Plus System classification highlights the highest performing Panasonic systems. — The air conditioner works in cooling mode with an outdoor temperature of -15°C. — The air conditioner works in heating mode even when outdoor temperatures are as low as -20°C.




DC Fan. Safe and precise. — R410A/R22 renewal. — Internet Control. A next generation system providing a user-friendly remote controller of air conditioning or heat pump units from everywhere, using a simple Android or iOS smartphone, tablet or PC via internet. — Danavai, a new way to connect. Simple and easy support tool with your smartphone. — BMS connectivity. The communication port can be integrated into the indoor unit and provides easy connection to, and control of, your Panasonic heat pump to your home or building management system. — 5 years compressor warranty.

The wall mounted units with stylish matt color can be offered for many applications such as studios, gyms, high ceiling areas and even computer server rooms. The compact design and flat face ensure discreet installation, even in a small space.

Closed discharge port

When the unit is turned OFF, the flap closes completely to prevent dust getting into the unit and to keep the equipment clean.



Air distribution is altered depending on the operational mode of the unit

Piping outlet in six directions

It is possible to place the piping outlet in six directions, right, right rear, right bottom, left, left rear and left bottom, making the installation work easier.

PACi R32 Refrigerant Gas

Panasonic recommends R32 because it is comparably environmentally friendly. Compared to R22 and R410A, R32 has a very low potential impact on global warming. Panasonic is leading the switch to R32.



New Commercial WLAN Adaptor

New CZ-CAPWFC1 interface adaptor, allows connection of one or a group of indoor units to be managed by the Panasonic Comfort Cloud App, which provides control, monitoring, scheduling and error alerts.



Datanavi, a new way to connect. Simple and easy support tool with your smartphone



Just holding up your smartphone to the LED display on a remote controller (CZ-RTC5B) to receive useful AC system information super fast by Panasonic Light ID Technology.

- Scan & Save AC system info
- Easy access to manual database
- Commissioning, F gas check data history



Remote controller	Cooling Capacity Nom (Min - Max) kW	SEER ¹⁾	Heating Capacity Nom (Min - Max) kW	SCOP ¹⁾	Indoor unit	Sound pressure ²⁾ dB(A)	Dimension (Ind) H x W x D mm	Outdoor unit ³⁾	Dimension (Out) H x W x D mm	Piping length range / Elevation difference (in/out) ⁴⁾ - m	
PACI ELITE. KIT-__H5 Single Phase / KIT-__H8 Three Phase.											
3,60kW	KIT-36PK2ZH5	3,60 (1,50 - 4,00)	8,00 A++	4,00 (1,50 - 5,00)	4,90 A++	S-36PK2E5B	35/31/27	302 x 1120 x 236	U-36PZH2E5	695 x 875 x 320	3 - 40 / 30
5,00kW	KIT-50PK2ZH5	5,00 (1,50 - 5,60)	7,60 A++	5,60 (1,50 - 6,50)	4,70 A++	S-50PK2E5B	40/36/32	302 x 1120 x 236	U-50PZH2E5	695 x 875 x 320	3 - 40 / 30
6,00kW	KIT-60PK2ZH5	6,10 (2,00 - 7,10)	7,20 A++	7,00 (1,80 - 8,00)	4,80 A++	S-60PK2E5B	47/44/40	302 x 1120 x 236	U-60PZH2E5	695 x 875 x 320	3 - 40 / 30
7,10kW	KIT-71PK2ZH5	7,10 (2,20 - 9,00)	6,80 A++	8,00 (2,00 - 9,00)	4,70 A++	S-71PK2E5B	47/44/40	302 x 1120 x 236	U-71PZH2E5	996 x 940 x 340	5 - 50 / 30
9,00kW	KIT-100PK2ZH5	9,50 (3,10 - 10,50)	6,40 A++	9,50 (3,10 - 11,50)	4,10 A+	S-100PK2E5B	49/45/41	302 x 1120 x 236	U-100PZH2E5	1416 x 940 x 340	5 - 85 / 30
7,10kW	KIT-71PK2ZH8	7,10 (2,20 - 9,00)	6,70 A++	8,00 (2,00 - 9,00)	4,70 A++	S-71PK2E5B	47/44/40	302 x 1120 x 236	U-71PZH2E8	996 x 940 x 340	5 - 50 / 30
9,00kW	KIT-100PK2ZH8	9,50 (3,10 - 10,50)	6,30 A++	9,50 (3,10 - 11,50)	4,10 A+	S-100PK2E5B	49/45/41	302 x 1120 x 236	U-100PZH2E8	1416 x 940 x 340	5 - 85 / 30
PACI STANDARD. KIT-__H5 Single Phase / KIT-__H8 Three Phase.											
6,00kW	KIT-60PK2Z5	6,10 (2,00 - 7,10)	6,80 A++	6,10 (1,80 - 7,00)	4,70 A++	S-60PK2E5B	47/44/40	302 x 1120 x 236	U-60PZ2E5	695 x 875 x 320	3 - 40 / 30
7,10kW	KIT-71PK2Z5	7,10 (2,00 - 7,70)	6,40 A++	7,10 (1,80 - 8,10)	4,60 A++	S-71PK2E5B	47/44/40	302 x 1120 x 236	U-71PZ2E5	695 x 875 x 320	3 - 40 / 30
9,00kW	KIT-100PK2Z5	9,00 (3,00 - 9,70)	6,50 A++	9,00 (3,00 - 10,50)	3,90 A	S-100PK2E5B	49/45/41	302 x 1120 x 236	U-100PZ2E5	996 x 980 x 370	5 - 50 / 30
9,00kW	KIT-100PK2Z8	9,00 (3,00 - 9,70)	6,50 A++	9,00 (3,00 - 10,50)	3,90 A	S-100PK2E5B	49/45/41	302 x 1120 x 236	U-100PZ2E8	996 x 980 x 370	5 - 50 / 30

Accessories	
CZ-RTC5B	Wired remote controller with Econavi function and datanavi
CZ-RWS3	Infrared remote controller
CZ-RE2C2	Simplified remote controller
PAW-GRDSTD40	Outdoor elevation platform 400x900x400mm

Accessories	
PAW-WTRAY	Tray for condenser water compatible with base ground support
PAW-GRDBSE20	Outdoor base ground support for noise and vibration absorption
PAW-PACR3	Interfaces to run 3 units on Backup and alternative run
CZ-CAPWFC1	NEW Commercial WLAN Adaptor

¹⁾ EER and COP calculation is based in accordance to EN14511. ²⁾ For models above 12kW, the SEER and SCOP is calculated based on values of EU/626/2011. For models below 12kW, the SEER and SCOP is calculated based on values of EU/2281/2016. ³⁾ The sound pressure of the units shows the value measured of the position 1m in front of the main body and 1m below the unit. The sound pressure is measured in accordance with Eurovent 6/C/1006-97 specification. ⁴⁾ Outdoor unit operation range : PZH - Cooling -15 ~ +46°C, Heating -20 ~ +24°C, PZ - Cooling -10 ~ +43°C, Heating -15 ~ +24°C. * Recommended fuse for the indoor 3A.



To find out how Panasonic cares for you, log on to: www.aircon.panasonic.eu

Panasonic Marketing Europe GmbH
Panasonic Air Conditioning
Hagenauer Strasse 43, 65203 Wiesbaden, Germany

heating & cooling solutions



Due to the ongoing innovation of our products, the specifications of this catalogue are valid. However, typographic errors, and may be subject to minor modifications by the manufacturer without prior warning in order to improve the product. The total or partial reproduction of this catalogue is prohibited without the express authorisation of Panasonic Marketing Europe GmbH.