

MXZ-2HA40VF COOLING

Indoor units combination	Cooling capacity (kW)			Outdoor unit power consumption(kW)	Current (A)			Power factor(%)
	Unit A	Unit B	Total		220	230	240	
25	2.50	-	2.50	0.600	2.90	2.78	2.66	94
			0.90 - 2.90	0.310 - 0.740				
35	3.40	-	3.40	0.920	4.45	4.26	4.08	94
			1.00 - 3.40	0.310 - 0.920				
25+25	2.00	2.00	4.00	1.010	4.88	4.67	4.48	94
			1.54 - 4.30	0.360 - 1.760				
25+35	1.69	2.31	4.00	0.970	4.69	4.49	4.30	94
			1.55 - 4.30	0.350 - 1.710				

MXZ-2HA40VF HEATING

Indoor units combination	Heating capacity (kW)			Outdoor unit power consumption(kW)	Current (A)			Power factor(%)
	Unit A	Unit B	Total		220	230	240	
25	3.15	-	3.15	1.270	6.64	6.35	6.08	87
			1.00 - 3.50	0.460 - 1.400				
35	3.60	-	3.60	1.440	7.52	7.20	6.90	87
			1.00 - 3.70	0.460 - 1.850				
25+25	2.15	2.15	4.30	0.910	4.75	4.55	4.36	87
			1.00 - 4.70	0.213 - 1.650				
25+35	2.01	2.29	4.30	0.910	4.75	4.55	4.36	87
			1.00 - 4.70	0.213 - 1.650				

MXZ-2HA50VF COOLING

Indoor units combination	Cooling capacity (kW)			Outdoor unit power consumption(kW)	Current (A)			Power factor(%)
	Unit A	Unit B	Total		220	230	240	
25	2.50	-	2.50	0.600	2.87	2.75	2.63	95
			0.90 - 2.90	0.310 - 0.800				
35	3.40	-	3.40	0.920	4.40	4.21	4.04	95
			1.00 - 3.40	0.310 - 0.920				
42	4.20	-	4.20	1.250	5.98	5.72	5.48	95
			1.30 - 4.50	0.340 - 1.480				
25+25	2.50	2.50	5.00	1.480	6.94	6.63	6.36	97
			1.54 - 5.40	0.360 - 1.930				
25+35	2.12	2.88	5.00	1.480	6.94	6.63	6.36	97
			1.55 - 5.40	0.350 - 1.920				
25+42	1.87	3.13	5.00	1.400	6.56	6.28	6.01	97
			1.56 - 5.40	0.350 - 1.680				
35+35	2.50	2.50	5.00	1.450	6.79	6.50	6.23	97
			1.56 - 5.40	0.340 - 1.750				

MXZ-2HA50VF HEATING

Indoor units combination	Heating capacity (kW)			Outdoor unit power consumption(kW)	Current (A)			Power factor(%)
	Unit A	Unit B	Total		220	230	240	
25	3.15	-	3.15	1.270	6.08	5.81	5.57	95
			1.00 - 3.50	0.460 - 1.400				
35	3.60	-	3.60	1.440	6.89	6.59	6.32	95
			1.00 - 3.70	0.460 - 1.850				
42	4.70	-	4.70	1.370	6.56	6.27	6.01	95
			1.30 - 5.40	0.460 - 1.850				
25+25	3.00	3.00	6.00	1.500	7.03	6.72	6.44	97
			1.11 - 6.40	0.170 - 2.060				
25+35	2.80	3.20	6.00	1.500	7.03	6.72	6.44	97
			1.12 - 6.40	0.160 - 2.050				
25+42	2.41	3.59	6.00	1.360	6.37	6.10	5.84	97
			1.12 - 6.40	0.160 - 1.840				
35+35	3.00	3.00	6.00	1.460	6.84	6.54	6.27	97
			1.12 - 6.40	0.150 - 1.990				

MXZ-3HA50VF COOLING

Indoor units combination	Cooling capacity (kW)				Outdoor unit power consumption(kW)	Current (A)			Power factor(%)
	Unit A	Unit B	Unit C	Total		220	230	240	
25	2.50	-	-	2.50 1.76 - 2.90	0.620 0.490 - 0.750	2.91	2.78	2.66	97
35	3.40	-	-	3.40 1.78 - 3.40	0.900 0.490 - 0.900	4.22	4.03	3.87	97
42	4.20	-	-	4.20 1.84 - 4.50	1.110 0.490 - 1.360	5.20	4.98	4.77	97
50	5.00	-	-	5.00 1.84 - 5.00	1.930 0.490 - 1.930	9.04	8.65	8.29	97
25+25	2.50	2.50	-	5.00 2.00 - 5.80	1.420 0.460 - 2.330	6.65	6.36	6.10	97
25+35	2.12	2.88	-	5.00 2.00 - 6.00	1.390 0.450 - 2.500	6.51	6.23	5.97	97
25+42	1.87	3.13	-	5.00 2.00 - 6.20	1.270 0.450 - 2.500	5.95	5.69	5.46	97
25+50	1.67	3.33	-	5.00 2.00 - 6.20	1.270 0.440 - 2.500	5.95	5.69	5.46	97
35+35	2.50	2.50	-	5.00 2.00 - 6.10	1.330 0.440 - 2.500	6.23	5.96	5.71	97
35+42	2.24	2.76	-	5.00 2.00 - 6.30	1.240 0.440 - 2.500	5.81	5.56	5.33	97
35+50	2.02	2.98	-	5.00 2.00 - 6.30	1.230 0.430 - 2.500	5.76	5.51	5.28	97
42+42	2.50	2.50	-	5.00 2.00 - 6.40	1.170 0.430 - 2.500	5.48	5.24	5.03	97
25+25+25	1.67	1.67	1.67	5.00 2.90 - 6.50	1.210 0.580 - 2.500	5.67	5.42	5.20	97
25+25+35	1.49	1.49	2.02	5.00 2.90 - 6.50	1.130 0.570 - 2.450	5.30	5.06	4.85	97

MXZ-3HA50VF HEATING

Indoor units combination	Heating capacity (kW)				Outdoor unit power consumption(kW)	Current (A)			Power factor(%)
	Unit A	Unit B	Unit C	Total		220	230	240	
25	3.15	-	-	3.15 1.00 - 3.50	1.270 0.460 - 1.400	5.95	5.69	5.46	97
35	3.60	-	-	3.60 1.00 - 3.70	1.440 0.460 - 1.480	6.75	6.45	6.19	97
42	4.70	-	-	4.70 1.30 - 5.40	1.370 0.460 - 1.550	6.42	6.14	5.88	97
50	5.40	-	-	5.40 1.40 - 6.50	1.550 0.460 - 2.650	7.26	6.95	6.66	97
25+25	3.00	3.00	-	6.00 1.50 - 7.00	1.540 0.240 - 2.440	7.22	6.90	6.62	97
25+35	2.80	3.20	-	6.00 2.19 - 7.20	1.520 0.290 - 2.700	7.12	6.81	6.53	97
25+42	2.41	3.59	-	6.00 2.20 - 7.40	1.440 0.290 - 2.690	6.75	6.45	6.19	97
25+50	2.21	3.79	-	6.00 2.20 - 7.40	1.420 0.290 - 2.690	6.65	6.36	6.10	97
35+35	3.00	3.00	-	6.00 2.19 - 7.30	1.510 0.290 - 2.690	7.08	6.77	6.49	97
35+42	2.60	3.40	-	6.00 2.20 - 7.40	1.430 0.290 - 2.690	6.70	6.41	6.14	97
35+50	2.40	3.60	-	6.00 2.20 - 7.50	1.410 0.280 - 2.680	6.61	6.32	6.06	97
42+42	3.00	3.00	-	6.00 2.22 - 7.50	1.380 0.280 - 2.690	6.47	6.19	5.93	97
25+25+25	2.00	2.00	2.00	6.00 1.45 - 7.50	1.210 0.220 - 2.120	5.67	5.42	5.20	97
25+25+35	1.91	1.91	2.18	6.00 1.45 - 7.50	1.200 0.200 - 2.120	5.62	5.38	5.15	97