

airHome 400

2.5 kW to 7 kW (R32), Heat pump



Key features

- Energy class up to A++/A++
- Integrated Wi-Fi
- FrostWash and Mould Guard technologies for healthier indoor air



RAK-DJ-RHAE

airHome 400 Wall Mounted System Inverter Heat Pump



| Model Reference | | Capacity (kW) | | | | | | | Max Pipe Length / Height (m) | Base Charge (m) / Additional Charge (g/m) | Pipe Size Gas / Liquid mm (in) | Fuse Rating (A) | Price (£) | | |
|-----------------|--------------|-------------------|-------------------|-----|------------|------------------|-----------------------|-----------------------|------------------------------|---|--------------------------------|-----------------|-----------|---------|--------|
| Indoor | Outdoor | Heating (nominal) | Cooling (nominal) | ERP | UK Cooling | Sensible Cooling | SCOP Based on EN14825 | SEER Based on EN14825 | | | | | Indoor | Outdoor | System |
| RAK-DJ18RHAE | RAC-DJ18WHAE | 2.5 (0.9-3.2) | 2.0 (0.9-2.5) | A++ | 2 | 1.93 | 4.60 | 7.50 | 20 / 10 | 20 / - | 9.52 (3/8") / 6.35 (1/4") | 16 | 172 | 513 | 685 |
| RAK-DJ25RHAE | RAC-DJ25WHAE | 3.4 (0.9-4.4) | 2.5 (0.9-3.1) | A++ | 2.50 | 2.21 | 4.60 | 7.50 | 20 / 10 | 20 / - | 9.52 (3/8") / 6.35 (1/4") | 16 | 247 | 505 | 752 |
| RAK-DJ35RHAE | RAC-DJ35WHAE | 4.2 (0.9-5.0) | 3.5 (0.9-4.0) | A++ | 3.50 | 2.78 | 4.60 | 7.50 | 20 / 10 | 20 / - | 9.52 (3/8") / 6.35 (1/4") | 16 | 290 | 583 | 873 |
| RAK-DJ50RHAE | RAC-DJ50WHAE | 6.0 (2.2-7.3) | 5.0 (1.9-5.2) | A++ | 5.00 | 3.37 | 4.50 | 7.00 | 20 / 10 | 20 / - | 9.52 (3/8") / 6.35 (1/4") | 25 | 391 | 759 | 1,150 |
| RAK-DJ60RHAE | RAC-DJ60WHAE | 6.8 (1.5-9.0) | 6.1 (1.7-7.4) | A++ | TBC | TBC | 4.10 | 6.80 | 30 / 20 | 30 / - | 12.7 (1/2") / 6.35 (1/4") | 20 | 476 | 943 | 1,419 |
| RAK-DJ70RHAE | RAC-DJ70WHAE | 8.1 (1.5-9.0) | 7.1 (1.8-7.4) | A++ | TBC | TBC | 4.00 | 6.20 | 30 / 20 | 30 / - | 12.7 (1/2") / 6.35 (1/4") | 20 | 565 | 1,166 | 1,731 |